

PACSystems™ RX3i I/O

Providing High Performance and Advanced Diagnostics

The PACSystems RX3i family provides advanced diagnostics and high performance I/O. With a modular design and multiple expansion options, RX3i is the perfect I/O solutionsolution for your process, hybrid, and discrete applications.

Modular, High-Speed Performance

RX3i is a rack-based system with a wide range of modules covering digital, analog, and numerous other specialty I/O types. These pluggable and hot-swappable modules allow you to customize the right mix of I/O, with a variety of voltage ranges and current capacities supported to meet all your application needs. Regardless of the I/O mix you choose, RX3i is built on high speed interfaces to provide rapid and consistent data transfer.

Highly Scalable

With the ability to pair I/O, RX3i allows you to scale your system with ease. In addition to I/O that you can put on the main rack, you can expand locally or remotely to connect to additional racks of I/O. In fact, RX3i can support as few as 8 I/O points and up to 32 thousand I/O points in a single system. With 7 to 16 slot backplanes and 1 slot expansion options, you can create the perfect system to fit your needs.

Perfect Upgrade Path

Emerson RX3i gives you a simple migration path and offers a quick and painless upgrade plan from legacy systems like Series 90-30, 90-70, and RX7i. RX3i allows you to re-use Series 90-30 modules on RX3i backplanes, so you can upgrade your I/O system without disturbing wires or buying new I/O. Upgrading to RX3i provides improved communications with integrated Ethernet along and modern USB for serial or memory sticks. With a smaller form factor, higher capacity, and speeds over 100 times faster than legacy controls, RX3i is an easy and cost effective upgrade to protect your investment without disruption. Upgrade in hours, not days!



High Availability

Eliminate process interruptions with RX3i I/O. Beyond just the high performance RX3i offers in simplex configurations, high availability configurations are also possible for maximum reliability. Both Ethernet Global Data (EGD) and PROFINET System Redundancy (PNSR) are supported. With gigabit speed and bumpless switchover, choosing RX3i high availability will prevent unexpected failure and costly downtime.

Rugged Connector Terminals

In the RX3i family all I/O modules have removal terminal blocks for easy commissioning and maintenance. This focus on ease of use is extended with the range of supported wire gauges. Depending on the Terminal block type chosen, the wire gauge ranges from 0.081mm² - 1.5mm² (28 - 14AWG) solid or stranded wire.

Spring style and box style modules are also both available for your preferred connection method. Terminal Block Quick Connect (TBQC) and positive retention are supported on both low density and high density terminal blocks to ensure confidence in wiring stability and a consistent commissioning experience.



Specifications

Mounting Format

- Panel Mount
- Rack Mount

Network Interfaces

- PROFINET
- Modbus/TCP
- Ethernet Global Data (EGD)
- Control Memory Exchange (CMX)
- PROFIBUS DP

Gateways / Bridges

- Serial Communications
- Modbus/RTU
- Modbus/TCP
- HART
- GENIUS
- DNP3 Serial/TCP
- IEC-61850
- IEC-104
- Reflective Memory
- PROFIBUS/Master
- CANOpen

Network Redundancy

- Media Redundancy Protocol (MRP)
- Dual LAN

System Redundancy

- PROFINET System Redundancy (PNSR)
- Ethernet Global Data (EGD)

I/O Redundancy

- Via Application Code

Media Support

- Copper
- SM Fiber
- MM Fiber

Media Connector

- 2x RJ45 and 2x SFP

I/O Types

- Digital
 - Voltage
 - TTL
 - Relay
- Analog
 - Voltage/Current
 - RTD
 - Thermocouple

Specialty Modules

- Pulse Test (24, 125 VDC)
- High Speed Counters
- Pulse With Modulation (PWM)
- Pulse Output
- Power Sync & Measure
- Strain Gauge
- SoE Inputs (application)

Isolation

- Galvanic Isolation
- DI, DO, AI, AO

Hot Swap

- Yes

Environmentals

- IP20
- 0 °C to 60 °C
- -40 °C to 60 °C options
- Conformal coat options

Agency Approvals

- UL
- UL HazLoc C1D2
- CE
- ATEX Zone 1

Marine (only select models)

- ABS
- BV
- DNV GL

Channel Density

- 2 - 32 points

Max Wire Gauge

- 12 (low density)
- 14 (high density)

Max I/O per Drop

- 448

I/O Family Comparison



| Product | PACSystems RSTi | PACSystems RSTi-EP | VersaPoint /VersaSafe | VersaMax Modular | VersaMax/IP | PACSystems RX3i | PAC8000 |
|------------------------------------|--|--|---|--|-------------------------------|--|---|
| Type | Distributed Slice | Distributed Slice | Distributed Slice | Chassis Based | On-machine Distributed | Chassis Based | Intrinsically Safe |
| Network Interfaces | PROFINET PROFIBUS DP Modbus/TCP Modbus/RTU DeviceNet | PROFINET PROFIBUS DP Modbus/TCP EtherCAT Ethernet/IP | PROFINET PROFIBUS DP Modbus/TCP DeviceNet | PROFINET PROFIBUS DP Modbus/TCP EGD DeviceNet GENIUS | PROFINET PROFIBUS DP | PROFINET PROFIBUS DP Modbus/TCP EGD CMX | PROFINET Modbus/TCP |
| System Redundancy | - | PNSR | - | PNSR, EGD or GENIUS | - | PNSR or EGD | PNSR or Modbus/TCP |
| Hot Swap | No | Yes | No | Yes | No | Yes | Yes |
| Environmentals | IP20 0 °C to 55 °C (UL) 0 °C to 60 °C (non-UL) | IP20 -20 °C to 60 °C | IP20 -20 °C to 55 °C | IP20 0 °C to 60 °C -40 °C to 60 °C (opt.) Conformal Coat (opt.) | IP67 -20 °C to 60 °C | IP20 0 °C to 60 °C -40 °C to 60 °C (opt.) Conformal Coat (opt.) | IP20 -40 °C to 70 °C Conformal Coat |
| Agency Approvals | UL UL HazLoc C1D2CE ATEX Zone 2 | UL UL HazLoc C1D2 CE ATEX Zone 2 | UL UL HazLoc C1D2 CE ATEX Zone 2 TUV SIL3 | UL UL HazLoc C1D2 CE ATEX Zone 2 | UL UL HazLoc C1D2 CE | UL UL HazLoc C1D2 CE ATEX Zone 2 | UL UL HazLoc C1D1 CE ATEX Zone 1 Intrinsically Safe |
| Marine | - | DNV GL | - | ABS, BV, DNV GL, LR (only select models) | - | ABS, BV, DNV GL (only select models) | LR |
| I/O Module Size (W x H x D) | 12 x 99 x 70 mm | 11.5 x 120 x 76mm | 12 x 120 x 70 mm | 66.8 x 163.5 x 70 mm | 70 x 178 x 49.3 mm | 34 x 145 x 140 mm | 42 x 110 x 106 mm |
| Typical Applications | Basic Machine | Machine Control Light Process Control General Automation | Functional Safety | Machine and Light Process Control General Automation | On-machine Cabinetless I/O | Complex Machine Process Control Motion Control General Automation | Harsh Environment Process Control |
| Level of Diagnostics | Good | Better | Best | Better | Good | Best | Best |

Ordering Information

| Part Number* | Description |
|-------------------------------|--|
| Power Supplies | |
| IC695PSA040 | Power Supply 120/240 Vac 125Vdc 40W |
| IC695PSD040 | Power Supply 24Vdc 40W |
| IC695PSD140 | Power Supply 24Vdc 40W Multi-purpose |
| IC695PSA140 | Power Supply 120/240 Vac 125Vdc 40W Multi-Purpose |
| IC694PWR321 | Power Supply 120/240 Vac 125Vdc 30W Serial Expansion |
| IC694PWR330 | Power Supply 120/240 Vac 125Vdc 30W High Capacity Serial Expansion |
| IC694PWR331 | Power Supply 24Vdc 30W High Capacity Serial Expansion |
| Discrete Input Modules | |
| IC694ACC300 | Input Simulator Module |
| IC694MDL230 | Input 120 Vac 8-Pt Isolated |
| IC694MDL231 | Input 240 Vac 8-Pt Isolated |
| IC694MDL240 | Input 120 Vac 16-Pt |

| | |
|--------------------------------|---|
| IC694MDL241 | Input 24Vac 16-Pt |
| IC694MDL250 | Input 120 Vac 16-Pt Isolated |
| IC694MDL260 | Input 120 Vac 32-Pt Grouped |
| IC694MDL632 | Input 125Vdc 8-Pt Pos/Neg Logic |
| IC694MDL634 | Input 24Vdc 8-Pt Pos/Neg Logic |
| IC694MDL635 | Input 125Vdc 16-Pt Pos/Neg Logic |
| IC694MDL645 | Input 24Vdc 16-Pt Pos/Neg Logic |
| IC694MDL646 | Input 24Vdc 16-Pt Pos/Neg Fast |
| IC694MDL648 | Input 48Vdc 16-Pt Pos/Neg Logic, 1ms filter |
| IC694MDL654 | Input 5/12Vdc (TTL) 32-Pt Pos/Neg |
| IC694MDL655 | Input 24Vdc 32-Pt Pos/Neg |
| IC694MDL658 | Input 48Vdc 32-Pt Pos/Neg Logic |
| IC694MDL660 | Input 24Vdc 32-Pt High-Density |
| IC695MDL664 | Input 24Vdc, 16-Pt, Pos Logic |
| Discrete Output Modules | |
| IC694MDL310 | Output 120 Vac 0.5A 12-Pt |
| IC694MDL330 | Output 120/240 Vac 2A 8-Pt |
| IC694MDL340 | Output 120 Vac 0.5A 16-Pt |
| IC694MDL350 | Output 120/240 Vac Isolated 16-Pt |
| IC694MDL390 | Output 120/240 Vac 2A 5-Pt Isolated |
| IC694MDL730 | Output 12/24Vdc 2A 8-Pt Positive Logic |
| IC694MDL732 | Output 12/24Vdc 0.5A 8-Pt Positive Logic |
| IC694MDL734 | Output 125Vdc 1A 6-Pt Isolated Pos/Neg |
| IC694MDL740 | Output 12/24Vdc 0.5A 16-Pt Positive Logic |
| IC694MDL741 | Output 12/24Vdc 0.5A 16-Pt Negative Logic |
| IC694MDL742 | Output 12/24Vdc 1A 16-Pt Positive Logic ESCP |
| IC694MDL752 | Output 5/24Vdc (TTL) 0.5A 32-Pt Negative Logic |
| IC694MDL753 | Output 12/24Vdc 0.5A 32-Pt Positive Logic |
| IC694MDL754 | Output 24Vdc 32-Pt High-Density |
| IC694MDL758 | Output 12/24Vdc 0.5A 32-Pt Positive Logic with ESCP per group |
| IC695MDL765 | Output 2 Amp 16-Pt Positive Logic |
| IC694MDL916 | Output 4 Amp 16-Pt Relay |
| IC694MDL930 | Output Relay N.O. 4 A 8-Pt Isolated |
| IC694MDL931 | Output Relay N.C. and Form C 3 A 8-Pt Isolated |
| IC694MDL940 | Output Relay N.O. 2 A 16-Pt |

| Discrete Mixed Modules | |
|--------------------------|--|
| IC694APU300 | High-Speed Counter Module |
| IC694APU305 | Special I/O Processor |
| IC695HSC304 | High-Speed Counter Module, 1.5MHz, 8 Inputs, 7 Outputs |
| IC695HSC308 | High-Speed Counter Module, 1.5MHz, 16 Inputs, 14 Outputs |
| IC694MDR390 | Mixed I/O 24Vdc Input (8-Pt) N.O. Relay Output (8-Pt) |
| Analog Input Modules | |
| IC695ALG106 | Analog Input Module, 6 Channel Isolated Voltage/Current |
| IC695ALG112 | Analog Input Module, 12 Channel Isolated Voltage/Current |
| IC694ALG220 | Input Analog 4pt Voltage |
| IC694ALG221 | Input Analog 4pt Current |
| IC694ALG222 | Input Analog 16 Single-Ended/8 Differential Voltage |
| IC694ALG223 | Input Analog 16 Single-Ended Current |
| IC694ALG232 | Input Analog 16 Channel Current |
| IC694ALG233 | Input Analog 16 Channel Voltage |
| IC695ALG306 | Isolated Thermocouple Input Module, 6 Channels |
| IC695ALG312 | Isolated Thermocouple Input Module, 12 Channels |
| IC695ALG412 | Isolated Thermocouple Input Module, 12 Channels |
| IC695ALG508 | Isolated RTD Input Module, 8 Channels |
| IC695ALG600 | Universal Analog Input Module, Voltage, Current, Resistance, RTD, TC |
| IC695ALG608 | Analog Input Module, 8 Channel Non-Isolated / 4 Channel Differential |
| IC695ALG616 | Analog Input Module, 16 Channel Non-Isolated / 8 Channel Differential |
| IC695ALG626 | Analog Input Module, 16 Channel Non-Isolated / 8 Channel Differential with HART Communications |
| IC695ALG628 | Analog Input Module, 8 Channel Non-Isolated / 4 Channel Differential with HART Communications |
| Analog Output Modules | |
| IC694ALG390 | Output Analog Voltage 2 Channels |
| IC694ALG391 | Output Analog Current 2 Channels |
| IC694ALG392 | Output Analog Current/Voltage 8 Channels |
| IC695ALG704 | Output Analog Current/Voltage 4 Channels |
| IC695ALG708 | Output Analog Current/Voltage 8 Channels |
| IC695ALG728 | Output Analog Current/Voltage 8 Channels with HART Communications |
| IC695ALG808 | Analog Output Current/Voltage 8 Channels, Isolated |
| Analog Mixed I/O Modules | |
| IC694ALG442 | Analog Module, 4-Inputs, 2-Outputs, Current/Voltage |
| IC694ALG542 | Analog Module, 4-Inputs, 2-Outputs, Current/Voltage with Advanced Diagnostics |

| Interface and Special Purpose Modules | |
|--|---|
| IC694BEM320 | I/O Link Interface Module |
| IC694BEM321 | I/O Link Master Module |
| IC694BEM331 | Genius Bus Controller Module |
| IC695CMM002 | Serial Communications Module, 2 Ports |
| IC695CMM004 | Serial Communications Module, 4 Ports |
| IC695CMX128 | Memory Exchange Module |
| IC694DNM200 | DeviceNet Master Module |
| IC694DSM314 | DSM314 Motion Controller |
| IC694DSM324 | DSM324 Motion Controller |
| IC695ECM850 | IEC 61850 Ethernet Communication Module |
| IC695EDS001 | RX3i DNP3 Outstation Module |
| IC695EIS001 | RX3i Ethernet 104 Server Module |
| IC695ETM001 | Ethernet Transmitter Module |
| IC695GCG001 | Genius Communications Gateway |
| IC695LRE001 | Serial Bus Transmitter Module |
| IC695NIU001 | Ethernet Network Interface Unit Module |
| IC695PBM300 | PROFIBUS Master Module |
| IC695PBS301 | PROFIBUS Slave Module |
| IC695PMM335 | PACMotion Multi-Axis Motion Controller |
| IC695PNC001 | PROFINET Controller Module |
| IC695PNS001 | PROFINET Scanner Module |
| IC695PNS101 | PROFINET Scanner Module for RX3i Sequence of Events |
| IC695PRS015 | Pressure Transducer Module |
| IC695RMX128 | Redundancy Memory Xchange Module, Multi-Mode Fiber |
| IC695RMX228 | Redundancy Memory Xchange Module, Single-Mode Fiber |
| Backplanes | |
| IC695CHS016 | RX3i 16-Slot Universal Backplane |
| IC695CHS012 | RX3i 12-Slot Universal Backplane |
| IC695CHS007 | RX3i 7-Slot Universal Backplane |
| IC694CHS392 | RX3i 10-Slot Serial Expansion Backplane |
| IC694CHS398 | RX3i 5-Slot Serial Expansion Backplane |
| IC693CHS392 | Series 90-30 10-Slot Expansion Backplane |
| IC693CHS398 | Series 90-30 5-Slot Expansion Backplane |
| IC693CHS393 | Series 90-30 10-Slot Remote Expansion Backplane |
| IC693CHS399 | Series 90-30 5-Slot Remote Expansion Backplane |

| | |
|--------------------|--|
| IC695CEE001 | RX3i CEE001 Expansion Carrier |
| IC695CEP001 | RX3i CEP001 Expansion Carrier with RJ-45 Copper |
| Accessories | |
| IC694ACC003 | RX3i Door labels for the IC694MDLxxx I/O modules |
| IC694ACC300 | RX3i DC Voltage Input simulator module |
| IC694ACC310 | RX3i Blank filler module |
| IC694ACC311 | RX3i Terminal blocks, 20 terminal (qty 6) for IC694xx I/O modules only. |
| IC695ACC002 | RX3i Replacement plastic cases for RX3i CPU and AC PS, quantity 4. Does not include front cover. |
| IC695ACC003 | RX3i Door labels for RX3i IC695xxx I/O modules LG728, IC695HSC304, IC695HSC308 |
| IC695ACC302 | RX3i Auxiliary Smart Battery Module |
| IC695ACC600 | RX3i Cold Junction Compensation Kit \ for Universal Analog Input IC695ALG600 |
| IC695ACC650 | RX3i Series 90-70 to RX3i Mechanical Frame |
| IC695ACC651 | RX3i SERIES 90-70 TO RX3I I/O ADAPTER CARD |
| IC695ACC652 | RX3i Series 90-70 to RX3i 5-Slot Conv Rack |

*add 'LT' suffix for low temp version, add 'CA' suffix for conformal coated version (not applicable for all modules)

United State Office

Emerson Automation Solutions
Intelligent Platforms, LLC
2500 Austin Dr
Charlottesville, VA

Singapore Office

Emerson Automation Solutions Intelligent
Platforms Asia Pacific Pte. Ltd.
1 Pandan Cres,
Singapore, 128461

Brazil Office

Emerson Automation Solutions
Av. Hollingsworth, 325 – Iporanga
Sorocaba – SP, 18087-105

China Office

Emerson Automation Solutions Intelligent
Platforms (Shanghai) Co., Ltd
No.1277, Xin Jin Qiao Rd, Pudong,
Shanghai, China, 201206

Germany Office

Emerson Automation Solutions
ICC Intelligent Platforms GmbH
Memminger Straße 14
Augsburg, DE 86159

India Offices

Emerson Automation Solutions
Intelligent Platforms Pvt. Ltd.,
Building No.8, Ground Floor
Velankani Tech Park, No.43
Electronics City Phase I, Hosur Rd
Bangalore-560100

Americas Support – Technical and Commercial

Phone: 1-888-565-4155 or 1-434-214-8532 (if toll free 800 option is unavailable)

Email for Technical Support: support.mas@emerson.com

Email for Commercial Support: customercare.mas@emerson.com

Primary language of support: English

Europe, Middle East, & Africa Support – Technical and Commercial

Phone: +800-4-444-8001

or +420-225-379-328 (if toll free 800 option is unavailable or dialing from a mobile telephone)

Email for Technical Support: support.mas.emea@emerson.com

Email for Commercial Support: customercare.emea.mas@emerson.com

Primary languages of support: English, German, Italian, Spanish

Asia Support – Technical and Commercial

Phone: +86-400-842-8599 for Greater China

+65-6955-9413 (All Other Countries)

Email for Technical Support: support.mas.apac@emerson.com

Email for Commercial Support Asia: customercare.cn.mas@emerson.com

Primary languages of support: Chinese, English

Support Website: www.emerson.com/iac-support

Home Website: www.emerson.com/industrial-automation-controls

©2020 Emerson. All rights reserved.

The Emerson logo is a trademark and service mark of Emerson Electric Co. All other marks are property of their respective owners. The contents of this publication are presented for information purposes only, and while effort has been made to ensure their accuracy, they are not to be construed as warranties or guarantees, express or implied, regarding the products or services describe herein or their use or applicability. All sales are governed by our terms and conditions, which are available on request. We reserve the right to modify or improve the designs or specifications of our products any time without notice.

